

Exceptional Design and Craftsmanship

William Russell Doors have been creating exceptional doors and entranceways since 1952.

William Russell Doors contemporary collection of unique internal and entry timber doors showcases the best in Australian and exotic timbers and craftsmanship.

As well as this stunning range, William Russell Doors can manufacture to just about any design and specification. From recreating a traditional masterpiece to helping create a totally modern custom design, creations can be customised to suit any particular architectural style.

William Russell has a team of master joinery craftsmen and can source an extensive range of timber species, such as Ash, Blackwood, Jarrah, Myrtle, Tasmanian Oak, Walnut, Sassafras, Victorian Ash or Western Red Cedar. Then incorporate glazing and metal features to create something purely individual.

Whether it's for residential homes or commercial projects, William Russell Doors can help you through the design process, no matter how intricate or grand.



Fusion Blade entrance door featuring red cedar and stainless steel inlay

Technical Information

STORAGE Always store your raw doors flat, in a dry place and avoid freshly plastered areas.

INSTALLATION All solid construction and external doors need to be hung with three hinges to provide sufficient support. The structural strength of the door must not be impaired in the fitting of the door, application of hardware, alterations or in excessive trimming of the door. If in doubt, please contact us for expert advice. Awnings are recommended for entrance doors exposed to weather.

TIMBER VARIATIONS The timber and veneers used in doors are a natural product that will have significant variation in colour and grain pattern. William Russell Doors will utilise its skills developed over 50 years to give you a quality product but these variations are unavoidable and will not be considered defects. Please note: Sassafras varies widely in appearance from one panel to another, consistency cannot be guaranteed.

EDGE STRIPS The timber used for matching timber edge strips will be matched to the door edge unless specified differently at time of order. As timber is a natural product there may be significant variation in colour and grain pattern. Timber edge strip thickness may vary due to the variance in moisture content, this is not considered a defect.

FINISHING OF DOOR Immediately after fitting and prior to hanging, the entire door including the top and bottom edges must receive at least three coats of varnish or sealer to prevent undue absorption of moisture or to prevent the timber drying out.

Exterior finishes shall be used on external doors and doors exposed to direct sunlight should be finished with light reflective colours, as dark colours can cause excessive heat absorption resulting in bowing, twisting and shrinkage. Direct sunlight will discolour timber doors where clear finishes are used as clear finishes are transparent to light

and offer limited protection. Semi gloss or satin finishes are recommended for all doors to reduce show-through.

Normal show-through of frame components in flush panel doors shall not be considered a defect. In particular, hard two pack finishes should not be used on joinery doors where normal movement will cause cracking of the finish. Please contact us for advice on the suitability of a particular door type for the paint finish you have selected.

The objective of finishing a door is to seal the timber; that is to prevent moisture absorption or loss. William Russell Doors will not accept responsibility for doors where the moisture content falls below 10% or exceeds 15%. Your paint supplier should be consulted as to the number of coats required to effectively seal the door. It is the responsibility of the owner to maintain an ongoing adequate seal, according to the paint supplier's recommendations, to prevent deterioration of the doors.

GUARANTEE William Russell Doors will not assume responsibility for doors, which became defective because of failure to follow these recommendations or for hazards of shipment or storage, after doors leave the control of the manufacturer. Doors must be inspected upon arrival for visible defects and all claims based thereon must be filed immediately. William Russell Doors agrees to repair or replace at its option, unfinished and in the form as originally supplied without charge, doors found to be defective within the meaning of this guarantee. Any such defects must be brought to the attention of the manufacturer promptly when discovered and in any event within five (5) years from the date of shipment by the manufacturer. William Russell Doors is not liable hereunder to reimburse the purchaser for doors repaired or replaced without prior written consent of the manufacturer to such repair or replacement. A warp not exceeding 5mm on doors up to 2134x914x38mm or 6mm on doors over 2134x914x38mm and up to 2438x914x38mm shall not be considered a defect. Doors in excess of 2438mm high or 1219mm wide are not guaranteed against bow or twist.



WWW.WRUSSELLDOORS.COM.AU

31 Koornang Road, Scoresby • Victoria • 3179

Ph: (03) 9763 1544 • Fax (03) 9764 2250



A JELD-WEN Company

William Russell Doors are available from Corinthian Doors:

SYDNEY: (02) 9673 7111 • MELBOURNE: (03) 9794 1122 • BRISBANE: (07) 3715 0100 • CAIRNS: (07) 4031 3888 • ADELAIDE: (08) 8243 0888 • PERTH: (08) 9455 1333

Disclaimer

Photographs or illustrations may not exactly depict the design or specification and may vary to actual.

We reserve the right to amend specifications at any time, without notice, in the interest of quality, performance and availability of materials.

William Russell Doors Pty Ltd

© William Russell Doors 2011

William Russell Doors Collection



the design possibilities are endless...

