



William Russell

Premium Timber Doors

A **JELD-WEN** Company



Pivot
HARMONY 3
Translucent



Pivot
HARMONY 2
Translucent



Pivot
HARMONY 1
Translucent



Pivot
BLADE
Jarrah



Infusion
FUSMJ 101
Jarrah



Infusion
FUSMM 101
Myrtle



Infusion
FUSMW 101
Walnut



Soho
SOHB
Blackwood



Tempus
TEMA 104
Translucent



Tempus
TEMA 04
Translucent



Seaboard
SEA
California
WRC Shiplap



Seaboard
SEAH
WRC Shiplap



Seaboard
SEAH 101
Translucent
WRC Shiplap



Joinery Glass
JOIN 9L
Clear Laminated



Joinery Glass
JOIN 10L
Clear Laminated



Joinery Glass
JOIN SL
Clear Laminated



Louvre
40mm Blades



Linea
LIN 3V
Translucent



Linea
LIN 7
Translucent



Linea
LIN 10
Translucent



Linea
LIN 5V
Grey Tint



Linea
LIN 5
Grey Tint



Linea
LIN 501
Grey Tint



Horizon
HOR 1V
Grey Tint



Horizon
HOR 3
Grey Tint



Horizon
HOR 701
Translucent



Horizon
HOR 5



Horizon
HOR 7



Victorian Entrance Frame
Cherry Oak Frame with Side Panels
and Overhead Transom featuring
Gainic Lead Lite



Victorian Entrance Frame
Cherry Oak Frame with Side Lites
featuring Edwardian Lead Lite



Victorian
EJ3



Victorian
EJ4
Heritage Lead Lite



Victorian
EJ5 & SLEJ
Edwardian Lead Lite





Tempus
TEMA 101 & SLTEMA 101
Grey Tint



Tempus
TEMA 105
Grey Tint



Tempus
TEMA 03
Grey Tint



Design Line
DL 204



Design Line
DL 4



Design Line
DL 6



Design Line
DL 12



Design Line
DL 201



Design Line
DL 202



Design Line
DL 203



Provincial
PRO 1



Provincial
PRO 2



Provincial
PRO 2L
Translucent



Provincial
PRO 3



Provincial
PRO 4



Feature Craftline
FC 1B



Feature Craftline
FC 4B



Feature Craftline
FCL 1
Bevelled Flower



Craftline
C 1



Craftline
C 3



Craftline
C 4



Craftline
CL 1
B3GC



Traditional
LPL6
Heritage Lead Lite



Traditional
APL9
Glue Chip



Victorian Line
NOVO



Victorian Line
V 1



Victorian Line
V 2



Victorian Line
V 4



Victorian Line
V 6



Victorian Line
V 8



Victorian Line
VL 2
Translucent



Victorian Line
VL 4
Translucent



1503 Centre Road, Clayton Victoria 3168
P(03) 9763 1544 F(03) 9764 2250
www.wrusselldoors.com.au

Range available via Corinthian Doors

Sydney (02) 9673 7100, Melbourne (03) 9794 1122, Perth (08) 9455 1333, Adelaide (08) 8243 0888, Brisbane (07) 3715 0100, Cairns (07) 4031 3888

Storage

Always store your raw doors flat, in a dry place and avoid freshly plastered areas.

Installation

All solid construction and external doors need to be hung with three hinges to provide sufficient support. The structural strength of the door must not be impaired in the fitting of the door, application of hardware, alterations or in excessive trimming of the door. If in doubt, please contact us for expert advice. Awnings are recommended for entrance doors exposed to weather.

Timber Variations

The timber and veneers used in doors are a natural product that will have significant variation in colour and grain pattern. William Russell Doors will utilise its skills developed over 50 years to give you a quality product but these variations are unavoidable and will not be considered defects. Please note: Sassafras varies widely in appearance from one panel to another, consistency cannot be guaranteed.

Edge Strips

The timber used for matching timber edge strips will be matched to the door edge unless specified differently at time of order. As timber is a natural product there may be significant variation in colour and grain pattern. Timber edge strip thickness may vary due to the variance in moisture content, this is not considered a defect.

Finishing of Door

Immediately after fitting and prior to hanging, the entire door including the top and bottom edges must receive at least three coats of varnish or sealer to prevent undue absorption of moisture or to prevent the timber drying out. Exterior finishes shall be used on external doors and doors exposed to direct sunlight should be finished with light reflective colours, as dark colours can cause excessive heat absorption resulting in bowing, twisting and shrinkage. Direct sunlight will discolour timber doors where clear finishes are used as clear finishes are transparent to light and offer limited protection. Semi-gloss or satin finishes are recommended for all doors to reduce show-through.

Normal show-through of frame components in flush panel doors shall not be considered a defect. In particular, hard two pack finishes should not be used on joinery doors where normal movement will cause cracking of the finish. Please contact us for advice on the suitability of a particular door type for the paint finish you have selected. The objective of finishing a door is to seal the timber; that is to prevent moisture absorption or loss. William Russell Doors will not accept responsibility for doors where the moisture content falls below 10% or exceeds 15%. Your paint supplier should be consulted as to the number of coats required to effectively seal the door. It is the responsibility of the owner to maintain an ongoing adequate seal, according to the paint supplier's recommendations, to prevent deterioration of the doors

Guarantee

William Russell Doors will not assume responsibility for doors, which became defective because of failure to follow these recommendations or for hazards of shipment or storage, after doors leave the control of the manufacturer. Doors must be inspected upon arrival for visible defects and all claims based thereon must be filed immediately. William Russell Doors agrees to repair or replace at its option, unfinished and in the form as originally supplied without charge, doors found to be defective within the meaning of this guarantee. Any such defects must be brought to the attention of the manufacturer promptly when discovered and in any event within five (5) years from the date of shipment by the manufacturer. William Russell Doors is not liable hereunder to reimburse the purchaser for doors repaired or replaced without prior written consent of the manufacturer to such repair or replacement. A warp not exceeding 5mm on doors up to 2134x914x38mm or 6mm on doors over 2134x914x38mm and up to 2438x914x38mm shall not be considered a defect. Doors in excess of 2438mm high or 1219mm wide are not guaranteed against bow or twist.

Note

Photographs or illustrations may not exactly depict the design or specification and may vary to actual. We reserve the right to amend specifications at any time, without notice, in the interest of quality, performance and availability of materials.

© William Russell Doors 2015 JWWNAT0074/0515